


DM2000 Series

DM2028 - DM2032



Kubota Models	DM2028	DM2032
Dimensions and Weight		
Cutting Width (ft)	9'2"	10'6"
Weight, approx. (lbs)	1345	1510
Transport Width (ft)	4'7"	4'7"
Attachment to Tractor		
Hitch (CAT)	2	2
Pin hitch	540	540
PTO (RPM)	50	55
Minimum PTO horsepower required (hp)		
Operation		
Number of disc and knives	8 / 24	8 / 24
Remotes	1	1
Cutterbar operating range °	-35 / +35	-35 / +35
Stubble height (in)	0.78"-1.97"	0.78"-1.97"
Other Features		
BreakAway	-	-
Non-Stop BreakAway	•	•
Overrun clutch	•	•
Friction clutch	-	-
Optional Equipment		
Swath boards (RH)	•	•
Swath discs (RH / LH)	o / -	o / -
High skids (inches) +0.8 / +1.6 / +3.2	• / o / o	• / o / o
Lighting kit	o	o
• = standard o = optional - = not available		

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purpose only. Some of the items pictured in this brochure are optional and not standard equipment. Please consult your local Kubota dealer for warranty, safety or product information. For your safety, Kubota strongly recommend the use of a seat belt in all applications.