

F90 Series

Specifications

F2690E/F2690/F3990



Model	F2690E		F2690	F3990
	2WD		4WD	
Engine				
Model	Kubota D1105		Kubota D1105	Kubota V1505T-IDI+DPF
Type	Liquid-cooled diesel (3 cyl)		Liquid-cooled diesel (4 cyl)	
Engine gross horsepower*	HP	25.5	25.5	39
Total displacement	cu.in. (cm ³)	68.6 (1,123)	68.6 (1,123)	91.4 (1,498)
Air cleaner	Type	Dual element		
	Air restriction indicator	N/A		Standard
Alternator		12 V, 40A		12 V, 60A
Fuel tank capacity	U.S. gals. (l)	16.1 (61.0)		
Transmission				
Type		HST (F2/R2)		
Max. travel speed	Forward / Reverse	mph (km/h)	12 (19.3)/6.2 (10)	
4WD mode select		N/A	Auto-assist 4WD with dual acting overrunning clutch/locked 4WD	
Differential lock			Standard	
Cruise control			Optional	
Tire				
Front		23x10.5-12	24x12-12	
Rear		16x6.5-8	18x9.5-8	
Brake				
		Wet discs		
Steering				
Type		Hydrostatic power		
Tilt steering		Standard		
Turn assist brake		Optional		
Dimension				
Tread (F/R)	in. (mm)	38.4 (975)/34.4 (875)	41.2 (1047)/39.3 (997)	
Wheel base	in. (mm)	51.2 (1,300)		
Overall length	in. (mm)	96.5 (2,450)	98.9 (2,510)	
Overall width	in. (mm)	48.8 (1,240)	53.9 (1,370)	
Overall height	in. (mm)	77.8 (1,975)	78.1 (1,985)	
Weight	lbs. (kg)	1,594 (723)	1,606 (730)	1,716 (780)
Ground clearance	in. (mm)	6.9 (175)	7.3 (185)	
Mower mounting				
Type		Independent live, Shaft drive		
PTO revolution		2,545	2,580	
Clutch		Wet multi discs, hydraulic		
Lift system		Hydraulic 2-point hitch		
Tilt angle	Degrees	90		
Tilt assist		Standard		
Weight transfer		Standard		
Others				
ROPS		Standard (ISO21299 and OSHA)		
Fuel gauge		LCD Display		
Tachometer		LCD Display		
Toolbox		Standard		
Seat		Reclining suspension seat		
Cup holder		Standard		

Mower Specifications

Model	RCK60P-F39	RCK72P-F39	RCK60R-F36	RCK72R-F36
Discharge	Side discharge		Rear discharge	
Cutting width	in. (mm)	60 (1,520)	72 (1,826)	60 (1,520)
Cutting height	in. (mm)	1 (25) - 5 (127)		
Cutting height adjustment	in. (mm)	Each 0.25 (6.4)		
Depth	in. (mm)	6.0 (152)	5.5 (140)	
Deck pan		Welded		
Thickness	in. (mm)	Top: 0.101 (4.2), Side 0.108(4.5)		0.108 (4.5)
Number of blades		3		
Front baffle kit		Standard		N/A
Mulch kit		Optional		

*SAEJ1995

The company reserves the right to change the above specifications without notice.

This brochure is for descriptive purpose only. Please contact your local Kubota dealer for warranty and safety information.

For your safety, KUBOTA strongly recommends the use of a Roll Over Protective Structure (ROPS) and seat belt in almost all applications.